





ethylbenzene which is classified as "possibly carcinogenic to humans" (2B) by IARC.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Pre-existing eye, skin and respiratory disorders may be aggravated.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: REMOVE TO FRESH AIR. IF BREATHING STOPS, GIVE ARTIFICIAL RESPIRATION. SPLASH (EYES): FLUSH EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. SPLASH (SKIN): WASH AFFECTED AREAS WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. INGESTION: DO NOT INDUCE VOMITING. IF VOMITING OCCURS SPONTANEOUSLY, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION OF LIQUID INTO THE LUNGS. GET MEDICAL ATTENTION IMMEDIATELY.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

REMOVE ALL SOURCES OF IGNITION AND PROVIDE VENTILATION. LARGE SPILLS MAY BE PICKED UP WITH NON-SPARKING TOOLS. SMALL SPILLS MAY BE PICKED UP WITH ABSORBENT MATERIALS. ADD WATER TO CONTAINERS. DO NOT ALLOW MATERIALS TO BECOME DRY.

WASTE DISPOSAL METHOD

Place in tightly closed containers and dispose of in accordance with local, state and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Store away from heat, sparks and open flames. Keep containers tightly closed when not in use. Use with adequate ventilation. Electrically bond and ground the drum while emptying. Do not allow contents to become dry.

OTHER PRECAUTIONS

Do not take internally. Avoid prolonged contact. Ground equipment to prevent accumulation of static charge.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

Use a NIOSH-approved respirator if exposure exceeds TLV limits.

VENTILATION

Use explosion-proof ventilation as required to control vapor concentrations.

PROTECTIVE GLOVES

Chemical resistant gloves

EYE PROTECTION

Chemical goggles, safety glasses

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Eye bath and safety shower

WORK/HYGIENIC PRACTICES

Wash hands thoroughly before eating or using the washroom. Smoke in smoking areas only.

## ===== SECTION IX - TRANSPORT INFORMATION =====

DOT (GROUND)

1.3 gallons (5 liters) or less:  
UN1263, Paint, 3, PGII, "Ltd. Qty."

Greater than 1.3 gallons (5 liters):  
UN1263, Paint, 3, PGII

AIR  
UN1263, Paint, 3, PGII

## ===== SECTION X - REGULATORY INFORMATION =====

CALIFORNIA PROPOSITION 65

This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Contains: Di(2-ethylhexyl) Phthalate -

This product contains a chemical known to the State of California to cause cancer.

Contains: Di(2-ethylhexyl) Phthalate - Ethylbenzene -

## ===== SECTION XI - DISCLAIMER =====

The information contained herein is based on the data available to us and is believed to be correct. However, PCL makes no warranty expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. PCL assumes no responsibility for injury from the use of the product described herein.